

Adapter cable: ACA 11

Description: The ACA 11 auto-configuration adapter saves the configuration data of the connected switch. It enables managed switched to be easily commissioned and quickly replaced.



Type: ACA 11

More Interfaces:

To the RS232 interface on the switch RJ11 connector

Power requirements:

Operating voltage via the RS232 interface on the switch

Service:

Diagnostics writing to ACA, reading from ACA, writing/reading not OK;
(display using LEDs on the switch)
Configuration via the RS232 interface of the switch and via SNMP/Web

Ambient conditions:

Operating temperature 0 °C to +60 °C
Storage/transport temperature -25 °C to +70 °C
Relative humidity (non-condensing) 10% to 95%

Mechanical construction:

Dimensions (W x H x D) 90 mm x 27 mm x 12 mm
Mounting plug-in module
Weight 35 g
Protection class IP 40
Cable length 31.5 cm

Mechanical stability:

IEC 60068-2-27 shock 15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration 1 g, 10 Hz - 150 Hz, 30 cycles

EMC interference immunity:

EN 61000-4-2 electrostatic discharge (ESD) 6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field 10 V/m

EMC emitted immunity:

EN 55022 EN 55022

Approvals:

Safety of industrial control equipment cUL 508 (E175531)
Hazardous locations cUL 1604 Class 1 Div 2 (E203960)
Safety of information technology equipment cUL 1950 (E168643)
Germanischer Lloyd Germanischer Lloyd (43 109-02 HH)

Scope of delivery and accessories:

Scope of delivery device, operating manual